

LPAS-320U Lightweight Portable Amplification System



Radio sold separately



LPAS-320U includes the popular A-320 30-512 MHz amplifier and a 90-512 MHz multiband antenna



Overview

The LPAS-320U (Lightweight Portable Amplification System) combines versatility and functionality in one packaged solution weighing less than 13 pounds. The LPAS includes the popular A-320* amplifier, an integrated MRC-93 rechargeable power supply and universal radio pocket. The universal pocket accepts 16 radios (including variants) fielded today. Optional accessories such as handset, speaker, and antennas are available.

Applications

The LPAS-320U is lightweight and highly portable. It is ideal for SATCOM-on-the-move (SOTM) applications where it can be quickly moved from vehicles to TOCs, or used as a manpack kit. The LPAS-320U is designed to accept lithium-ion, lithium, nickel metal hydride, sealed lead acid batteries, or a wide range of AC and DC inputs.

*LPAS-320U compatible with A-320V1 amplifier ONLY.

Features

- ▶ **Universal radio pocket accepts 16 radios (including variants - see reverse)**
- ▶ **Includes A-320 30-512 MHz amplifier**
- ▶ **90-512 MHz multiband antenna**
- ▶ **Integrated power supply**
- ▶ **AC/DC power cables**

LPAS-320U Lightweight Portable Amplification System



LPAS-320U Features:

AC Input	95-265 VAC
DC Input	11-36 VDC
Radio Pocket	Universal
Size (inches)	10.35(W) x 11.3(L) x 3.5(H)

Environmental Qualifications	MIL-STD-810G
------------------------------	--------------

Temperature
Shock
Vibration
Altitude
Humidity
Rain
Salt Fog
Sand & Dust

Reliability	+15,000 hours
-------------	---------------

MRC-93 Power Supply Indicators:

Battery	•
Charging	•
AC Operation	•
DC Operation	•

MRC-93 Features:

AC Input	95-270 VAC, 47-440 Hz
----------	-----------------------

DC Input	9-36 VDC
----------	----------

DC Output	26.5 VDC @5.5 amps (7 amps peak)
-----------	-------------------------------------

Size	3.27"H x 10.6"W x 6.25"D
------	--------------------------

Weight	3.75 lbs. (w/o battery)
--------	-------------------------

Cables Included	PCP-35 AC input PCP-65 DC input
-----------------	------------------------------------

Cables (Optional)	PCP-55 Auto - DC w/banana plugs PCP-40 DC input PCP-235 NATO input
-------------------	--

A-320 Amplifier Features:

Frequency	30-512 MHz (full-spectrum)
-----------	----------------------------

RF Input	5 watts (nominal)
----------	-------------------

RF Output (FM)	20 watts
----------------	----------

RF Output (AM)	20 watts PEP/110-512 MHz
----------------	--------------------------

Power	18-36 VDC
-------	-----------

SINCGARS/ HAVEQUICK	Compatible
------------------------	------------

RF Connector (RAD/ANT)	BNC/TNC
---------------------------	---------

Operating Temp.	-40° to +60° C
-----------------	----------------

Weather Resistant	Yes
-------------------	-----

Finish	Black, Anodized
--------	-----------------

Supported Radios:

Thales AN/PRC-148 MBITR

Thales AN/PRC-148 JEM

Harris AN/PRC-152(C) family V1-V6

Harris RF-5800M

Harris RF-5800V

Harris RF-7800HH

Harris RF-310M-HH01

Harris RF-310M-HH02

Harris RF-1033M-PR001

Harris RF-1033M-PR002

ITT Soldier Radio

Supported Power Supplies:

MRC-82A (Li-Ion)

MRC-92 (multichemistry)

MRC-93 (multichemistry)

MRC-99 (Lead Acid)

MRC-132 (Ni-MH)

PSU-40

HARRIS, Falcon II and Falcon III
are registered trademarks of Harris Corporation