

# CH0014

## Technical Datasheet



### Features

- LED status indicator
- Contains charge control module, universal power supply, line cord and cable/connector

### Benefits

- Specifically designed to charge Ultralife UBBL09 battery safely and efficiently
- Safety circuit protects against charging shorted packs

### Applications

- Commercial desktop charger for UBBL09 battery

### Technical Specifications

<b>Part No.</b>	CH0014
<b>DC Input</b>	19-30VDC
<b>DC Output</b>	12.6V
<b>Charge Rate</b>	2.0A
<b>Battery Types</b>	Li-Ion
<b>User Interface</b>	Off: No battery detected Green blinking: Charging Green steady on: Charge complete Red blinking: Error - shorted terminals, invalid pack chemistry
<b>Connectors</b>	Input: 2.5mm Center Positive
<b>Color</b>	Black
<b>Finish</b>	Case Material: ABS G1SM
<b>Size</b>	Charger: 174mm (6.85in) x 124mm (4.88in) x 54mm (2.12in) Charger Cable: 60.9cm (24in)
<b>Weight</b>	460g (16.2oz)
<b>Operating Temperature</b>	0°C to 45°C
<b>Storage Temperature</b>	-25°C to 70°C
<b>Accessories Included</b>	Power Supply - PS2524 Input Voltage: 100-240VAC, 47-63Hz Output Voltage: 24VDC Input Connector: IEC-320 Output Cable: 18Awg, 1.83m (6ft) Weight: 300g (10.5oz)
<b>Accessories Optional</b>	Line Cord - UL/CSA 3 prong (North America), length 1.83m (6ft) CA0003 - Vehicle Power Adapter Line Cords: USA: 1090-01-0002 AUS: 1090-01-0004 EUR: 1090-01-0008