

4030


Low Rate AAA Cell
Lithium Thionyl Chloride

Electrochem 100LR Series

Physical Characteristics

Cell Drawing


Chemistry	Thionyl Chloride
Construction	Bobbin
Cell Size	Sub AAA
Length¹	25.4 mm
Diameter²	10.2 mm
Cell Weight	5.0 g
Lithium Weight	0.2 g
Integrated Safety Fuse	N/A



Electrical Characteristics

Cell Type	Primary
Open Circuit Voltage (25°C)	3.67 V
Nominal Capacity	0.51 Ah
Maximum Continuous Current	10 mA
Operating Temperature	-40°C to +100°C
Self Discharge Rate	<2% per year
Storage Temperature	≤25°C
Discharge Condition	2 mA, 23°C

Discharge Curve
2 mA, 25°C



Key Features

- Primary chemistry (non-rechargeable)
- Low rate capability
- Bobbin style construction
- Stainless steel container
- Hermetic glass-to-metal sealing
- Custom terminations available

Main Applications³

- Memory back-up
- Animal telemetry
- Low current downhole oil and gas

NOTE: ¹ The information on this datasheet is for marketing purposes only. Please consult with Electrochem for more information regarding how our cells will perform within your application.

² The information in this document is subject to change without notice and does not constitute a warranty of performance. ³ This product and its external electrical contact materials are RoHS compliant. See our "RoHS Statement" for more information. ⁴ The length dimension was based off of a flat termination. The use of other terminations will impact overall cell length.

⁵ Diameter measurements include shrink when applicable. ⁶ The "Main Application" list does not include all potential applications, please consult Electrochem for your application needs.

ULTRALIFE®

670 Paramount Drive, Raynham, MA 02767 USA
ph 781.830.5800 • fax 781.575.1545 • www.ulbi.com

Rev. 0001