

A-320V3A-KT

30-512 MHz Amplifier Kit

Technical Datasheet

WE. ARE. CRITICAL. POWER.™



Overview

The A-320V3A-KT supports the latest TDMA waveforms including Soldier Radio Waveform (SRW) and Enhanced Position & Location Reporting System (EPLRS). The amplifier maintains support for legacy communications modes including HAVEQUICK, SINCGARS, and DAMA.

The amplifier itself weighs a mere 24 ounces, and the entire kit weighs less than 3.1 pounds.

Kit Components

- A-320V3A amplifier
- 90-512 MHz multiband antenna
- 30-108 MHz antenna
- Antenna mount
- Amplifier holster with MOLLE vest adapter
- RF cables
- Power cable

Features

- 30-512 MHz
- Supports new waveforms:
 - SRW (Soldier Radio Waveform)
 - EPLRS (Enhanced Position & Location Reporting System)
- AM operation

Includes A-320V3A Amplifier with these Technical Specifications

Part No.	A-320V3A
NSN	5996-01-560-2777
Size H x W x D (inches)	1.5 x 3.75 x 5.5
Weight	24 oz. (680 g.)
Frequency Range	30-512 MHz
Input/Output Impedance	50 ohms
RF Input	5 watts (nominal)
RF Output - FM	20 watts
RF Output - AM	20 watts PEP/110-512 MHz
RX Path Insertion Loss	< 1.5 dB
RX Path VSWR	< 2:1
Bypass Path Insertion Loss	< .5 dB
Power	18-36 VDC
Power @ Transmit	~ 65 watts
Power @ Receive	< 3.0 watts
RF Connector RAD/ANT	BNC/TNC female
Operating Temperature	-40°C to +60°C
Noise Figure	< 3dB
1 dB Compression	22 dBm
Weather Resistant	MIL-STD 810F (submersible 1M for 30 mins.)
EMI	MIL-STD 461E
Finish	Green, anodized

Indicators

Power ON/OFF	•
Power Set	7, 10, 15, 20 watts
TX Active	•
RX Active	•
VSWR Fault	•
FM	•
AM	•
SYS/CUR	•
Battery	•
Over Temperature	•